

Across Collection

VOXFLOOR®


Technical Specifications

Style Name	Above Woods A
Total Thickness	5mm
Wear Layer Thickness	0.5mm
Wear Layer Treatment	UV
Tile Size	25cm*100cm
Backing	Loose lay
Pieces per box	8 pcs/box (2 m2)
Usage Classification	42 Light Industrial General 33 Commercial Heavy



ANSI ACCREDITED PROGRAM
PRODUCT CERTIFICATION
#0821

Installation Method



Performance Specifications

	Test Code	Standard	Test Result
Flammability Test	EN13501	Bfl-S1	Pass
Slip resistance Test	EN13893:2002	DS	Pass
Formaldehyde Test	EN717-1	E1	Pass
Color Fastness to artificial light	ISO 105-B02:2014 Method 3	≥Grade 6	Pass
Residual indentation	ISO 24343-1:2007	Average value: ≤0.1mm	Pass
Dimensional stability after exposure to heat	ISO 23999:2008	≤0.25%(tiles intended for dry-joint laying) ≤0.4%(sheets and tiles intended for heat welding)	Pass
Curling after exposure to heat	ISO 23999:2008	≤2mm(tiles intended for dry-joint laying) ≤8mm(sheets and tiles intended for heat welding)	Pass
Effect of castor chair	ISO 4918:2016	After 25,000 cycles, no delamination shall occur. No disturbance to the surface other than a slight change in appearance	Pass
Composition	PVC, DOTP, Calcium Carbonate, Fiber Glass		

NOTE: All Product Specifications are averages derived from product sample testing and are subject to normal manufacturing normal manufacturing tolerances and testing tolerances. Product Specifications may be changed without notice as long as product performance is not materially affected.