

# Across Collection

# VOXFLOOR®


## Technical Specifications

Style Name	Above Woods B
Total Thickness	5mm
Wear Layer Thickness	0.5mm
Wear Layer Treatment	UV
Tile Size	25cm*100cm
Backing	Loose lay
Pieces per box	8 pcs/box (2 m2)
Usage Classification	42 Light Industrial General 33 Commercial Heavy




ANSI ACCREDITED PROGRAM  
PRODUCT CERTIFICATION  
#0821

Installation Method



Ashlar



Herringbone

## Performance Specifications

	Test Code	Standard	Test Result
<b>Flammability Test</b>	EN13501	Bfl-S1	Pass
<b>Slip resistance Test</b>	EN13893:2002	DS	Pass
<b>Formaldehyde Test</b>	EN717-1	E1	Pass
<b>Color Fastness to artificial light</b>	ISO 105-B02:2014 Method 3	≥Grade 6	Pass
<b>Residual indentation</b>	ISO 24343-1:2007	Average value: ≤0.1mm	Pass
<b>Dimensional stability after exposure to heat</b>	ISO 23999:2008	≤0.25%(tiles intended for dry-joint laying) ≤0.4%(sheets and tiles intended for heat welding)	Pass
<b>Curling after exposure to heat</b>	ISO 23999:2008	≤2mm(tiles intended for dry-joint laying) ≤8mm(sheets and tiles intended for heat welding)	Pass
<b>Effect of castor chair</b>	ISO 4918:2016	After 25,000 cycles, no delamination shall occur. No disturbance to the surface other than a slight change in appearance	Pass
<b>Composition</b>	PVC, DOTP, Calcium Carbonate, Fiber Glass		

NOTE: All Product Specifications are averages derived from product sample testing and are subject to normal manufacturing normal manufacturing tolerances and testing tolerances. Product Specifications may be changed without notice as long as product performance is not materially affected.